

# Generador

## Generador SC-C

Generador SC-C1  
25KVA-215KVA @ 50Hz  
Especificaciones

Modelo	Motor	Potencia principal		Energía de espera		Peso neto (KG)	Dimensiones(mm)			Consumo de combustible L/hr	Modelo de capa insonorizada
		KVA	KW	KVA	KW		L	M	H		
SD-C20	4BT3.9-G	22	18	24	20	628	1780	715	1150	5.0	K2600/H2600
SD-C30	4BT3.9-G	30	24	33	26	628	1780	715	1150	6.5	K2600/H2600
SD-C40	4BT3.9-G	42	34	46	37	900	1780	715	1150	9.3	K2600/H2600
SD-C50	4BTA3.9-G	50	40	55	44	900	1800	720	1200	12.0	K2600/H2600
SD-C60	4BTA3.9-G	63	50	69	55	900	1800	720	1200	14.0	K2600/H2600
SD-C70	6BT5.9-G	70	55	77	61	920	2000	800	1300	16.0	K3050/H3000
SD-C90	6BT5.9-G	90	75	100	83	950	2000	800	1300	20.0	K3050/H3000
SD-C100	6BTA5.9-G	100	80	110	88	980	2250	830	1350	22.0	K3350/H3200
SD-C110	6BTAA5.9-G	113	90	124	99	1100	2250	830	1350	23.0	K3350/H3200
SD-C125	6BTAA5.9-G	125	100	138	110	1150	2250	830	1350	27.0	K3350/H3200
SD-C140	6CTAA8.3-G	137	110	150	120	1180	2500	860	1350	30.0	K3350/H3200
SD-C160	6CTA8.3-G	160	128	176	140	2200	2500	860	1350	32.0	K3900/H3500
SD-C190	6CTA8.3-G	190	152	209	168	2200	2500	860	1350	39.0	K3900/H3500
SD-C200	6CTAA8.3-G	200	160	220	176	2400	2600	880	1500	41.0	K3900/H3500
SD-C215	6CTAA8.3-G	215	172	236	189	2400	2600	880	1500	45.0	K3900/H3500

20KVA-220KVA @ 60Hz  
Especificaciones

Modelo	Motor	Potencia principal		Energía de espera		Peso neto (KG)	Dimensiones(mm)			Consumo de combustible L/hr	Modelo de capa insonorizada
		KVA	KW	KVA	KW		L	M	H		
SD-C20/6	4BT3.9-G	22	18	24	20	628	1780	715	1150	5.0	K2600/H2600
SD-C30/6	4BT3.9-G	30	24	33	26	628	1780	715	1150	6.5	K2600/H2600
SD-C45/6	4BT3.9-G	45	36	50	40	900	1780	715	1150	9.3	K2600/H2600
SD-C60/6	4BTA3.9-G	63	50	69	55	900	1800	720	1200	14.0	K2600/H2600
SD-C70/6	6BT5.9-G	70	55	77	61	920	2000	800	1300	15.4	K3050/H3000
SD-C85/6	6BT5.9-G	85	68	94	75	920	2000	800	1300	18.7	K3050/H3000
SD-C100/6	6BT5.9-G	100	80	110	88	920	2000	800	1300	22.0	K3050/H3000
SD-C115/6	6BTAA5.9-G	115	93	138	103	1150	2250	830	1350	27.0	K3350/H3200



SD-C265/6	NTA855-G1	265	212	292	233	2900	3100	980	1850	58	K4920/H4300
SD-C310/6	NTA855-G1	313	250	344	275	2900	3100	980	1850	69	K4920/H4300
SD-C340/6	NTA855-G1B	344	275	378	303	3100	3100	980	1850	70	K4920/H4300
SD-C390/6	NTA855-G1B	394	315	483	350	3100	3100	980	1850	76	K4920/H4600
SD-C435/6	KTA19-G2	438	350	481	385	4300	3560	1246	1950	82	K4920/H4600
SD-C510/6	KTA19-G3	513	410	564	451	4400	3560	1246	1950	100	K4920/H4600
SD-C560/6	KTA19-G4	562	450	619	495	4500	3560	1246	1950	112	K5320/H5200
SD-C625/6	KTAA19-G5	625	500	688	550	4700	3760	1246	1950	130	K5320/H5200
SD-C735/6	KTAA19-G6A	738	590	811	649	5000	4400	1769	2300	130	K5800/H5600
SD-C735/6#	KTAA19-G7	738	590	811	649	5000	4400	1769	2300	138	K5800/H5600
SD-C775/6	KT38-G	775	620	853	682	8000	4630	1900	2640	148	available
SD-C875/6	KT38-G2	875	700	963	770	8400	4730	1900	2640	165	available
SD-C1000/6	KTA38-G2A	1000	800	1100	880	8500	4780	1900	2640	200	available
SD-C1125/6	KTA38-G4	1125	1000	1237	1100	8500	4780	1900	2640	215	available

Las especificaciones y el diseño están sujetos a cambiarse sin aviso.