

Generador

Generador SC-M

Generador SC-M
600KVA-2000KVA @ 50Hz
Especificaciones

Modelo	Motor	Potencia principal KVA KW		Energía de espera KVA KW		Peso neto (KG)	Dimensiones(mm) L M H			Consumo de combustible L/hr	Modelo de capa insonorizada
SD-M600	S6R-PTA	600	480	660	520	4619	3635	1460	1720	125	K5320
SD-M650	S6R2-PTA	650	520	750	600	4979	3635	1460	1720	155	K5320
SD-M750	S6R2-PTAA	750	600	820	660	5480	4080	1715	1985	174	available
SD-M910	S12H-PTA	910	728	1000	800	7869	4450	1645	2400	234	available
SD-M1050	S12H-PTA	1050	840	1160	928	8276	4450	1645	2400	241	available
SD-M1275	S12R-PTA	1275	1020	1425	1140	10000	4665	1890	2650	282	available
SD-M1375	S12R-PTA2	1375	1100	1530	1224	11850	4700	2225	2891	315	available
SD-M1500	S12R-PTAA2	1500	1200	1650	1320	12980	4920	2192	3056	333	available
SD-M1735	S16T-PTA	1735	1388	1900	1520	13000	5650	2580	3005	375	available
SD-M1900	S16R-PTA2	1906	2100	1525	1680	14400	5650	2580	3005	408	available
SD-M2000	S16R-PTAA2	2000	1600	2250	1800	16000	5700	2390	3360	432	available